


PRODUCT DATA SHEET

Product ID:

RGH1

Product Name:

Rear D Safety Harness







This one point safety harness comes with a single rear attachment point.

This safety harness is to be used primarily with a fall arrest safety lanyard to provide basic fall protection.

If combined with a twin leg lanyard (RGL3) the safety harness can be used for tower climbing, scaffold work and general steel erecting.

Suitable for use with fall arrest blocks, however we recommend the addition of the RGL4 extension strop to facilitate easy connection.

Accredited to:

EN 361:2002

Web material:

45mm water repellent polyester

Fittings:

High tensile steel alloy

Weight:

1.0kg

Size Guide:

Size	Small	Standard	Large	X-Large
A	36 - 42"	42 - 50"	50 - 54"	54 - 58"
Chest	91 - 106cm	106 - 127cm	127 - 137cm	137 - 147cm
B	30 - 36"	36 - 44"	44 - 48"	48 - 52"
Waist	76 - 91cm	91 - 111cm	111 - 121cm	121 - 132cm
C	38 - 44"	44 - 52"	52 - 56"	56 - 60"
Hips	96 - 111cm	111 - 132cm	132 - 142cm	142 - 152cm



Staffordshire, ST13 6BB, UK



Features:





Rip stitch indicators



Rear attachment point

