

# McKissick® Snatch Blocks

**Fatigue Rated**



**SEE APPLICATION AND WARNING INFORMATION**

Para Español: [www.thecrosbygroup.com](http://www.thecrosbygroup.com)

On Pages 375-382

## 418 WITH HOOK



### New Improved Light Champion

- Forged alloy heat treated hooks.
- Forged steel swivel tees, yokes and shackles.
- Hook and shackle assemblies on 4-1/2" through 14" sizes can be interchanged.
- Can be furnished with bronze bushings or roller bearings.
- Opening feature permits insertion of rope while block is suspended from gin-pole.
- 3" thru 18" 418 and 419 blocks have exclusive bolt retaining spring to assure no lost bolts.
- Can be furnished with S-4320 hook latch.
- Pressure lube fittings.
- 3" - 10" feature dual rated wireline sheaves.
- Fatigue rated.
- 4-1/2" and larger are **RFID EQUIPPED**.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these blocks meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26.



## 419 WITH SHACKLE



### 418 / 419 / 404 Snatch Blocks

Sheave Diameter (in.)	Bearing Code	Stock No.			Wire Rope Size (mm)	Working Load Limit (t)*	Weight Each (kg.)			Rep. Sheave Stock No.	Rep. Latch Stock No.
		418 with Hook	419 with Shackle	404 Tail Board			418 with Hook	419 with Shackle	404 Tail Board		
* 3	BB		109091	—	8-10	2	—	1.90	—	460147	—
** 3	BB	108038	109037 †	102016	8-10	2	2.04	1.81	1.22	460147	1096421
**4-1/2	BB	108065	109064	102025	10-13	4	5.31	5.44	2.99	2000232	1096468
6	BB	108127	109126	102098	16-19	8	12.2	12.6	6.80	460815	1096562
6	RB	108154	109153	102114	16-19	8	12.2	12.6	6.80	472688	1096562
8	BB	108225	109224	102169	16-19	8	15.0	15.4	9.53	461164	1096562
8	RB	108252	109251	102187	16-19	8	15.0	15.4	9.53	473277	1096562
10	BB	108323	109322	102230	16-19	8	18.6	19.1	13.2	461805	1096562
10	RB	108350	109359	102258	16-19	8	18.6	19.1	13.2	473776	1096562
12	BB	169169	202961	178890	16	8	21.8	22.2	16.3	462270	1096562
12	RB	199911	169347	178934	16	8	21.8	22.2	16.3	474141	1096562
12	BB	108421	109420	102301	19	8	21.8	22.2	16.3	462289	1096562
12	RB	108458	109457	102329	19	8	21.8	22.2	16.3	474150	1096562
14	BB	194920	169356	—	16	8	24.9	25.4	—	463625	1096562
14	RB	199948	167857	—	16	8	24.9	25.4	—	474766	1096562
14	BB	108528	109527	—	19	8	24.9	25.4	—	463634	1096562
14	RB	108546	109545	—	19	8	24.9	25.4	—	474775	1096562
16	BB	199975	203041	—	19	15	59	61	—	4100056	1096609
16	RB	200008	203087	—	19	15	59	61	—	4200028	1096609
16	BB	108608	109607	—	22	15	59	61	—	4100065	1096609
16	RB	108626	109625	—	22	15	59	61	—	4200037	1096609
18	BB	200099	203130	—	22	15	68	70	—	464571	1096609
18	RB	200151	203176	—	22	15	68	70	—	475792	1096609
18	BB	108644	109643	—	26	15	68	70	—	4104640	1096609
18	RB	108662	109661	—	26	15	68	70	—	6000000	1096609

\* Ultimate Load is 4 times the Working Load Limit.

\*\* Available in Bronze Bushed only. 3" and 4-1/2" have self lubricating Bronze Bushing.

† Fitted with 1-1/4" ID Swivel Eye.

‡ May be furnished in other rope sizes.

NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing, and wire rope size.

NOTE: Tail Board does not contain the spool that is required with the hook (418) and shackle (419) snatch blocks.

## 404 TAIL BOARD



McKissick Blocks