## **CG** 'STANDARD' GIRDER TURNING CLAMPS

For longer girders use two clamps and a lifting beam



The main purpose of **the CG girder turning clamps** is for the transportation and turning of steel girders (RSJ) through 90° degrees.

They can be used individually or for longer beams used in pairs in conjunction with a spreader beam as shown in diagram.

The clamps are attached to the horizontal flange of the girder and locked in place by the jaw locking lever. Once lifted the girder will turn through 90° degrees.


Model	WLL	Jaw capacity	Weight	Price
	kg*	mm	kg*	£*
CG 1	100 - 1000	0 - 16	6	£225
CG 2	200 - 2000	0 - 32	14	£294
CG 4	400 - 4000	0 - 32	19	£399
CG 6	600 - 6000	12 - 50	37	£515
CG 8	800 - 8000	12 - 50	40	£617

<sup>\*</sup>Per clamp.

## TTR 'VERTICAL FLANGE' GIRDER STACKING CLAMPS



The main selling point of **the TTR girder stacking clamps** is the fact that it enables girders to be transported and stacked horizontally. These are ideal for use within steel stockholders. Once offered up to the **vertical** flange of the girder, they are locked in place by the jaw locking lever.





Model	WLL kg*	Jaw capacity mm	Weight kg*	Price £*
TTR 750	50 - 750	5 - 16	3.5	£298
TTR 1500	150 - 1500	5 - 25	10	£316
TTR 3000	300 - 3000	5 - 28	12	£517

<sup>\*</sup>Per clamp.


## TTG 'HORIZONTAL FLANGE' GIRDER STACKING CLAMPS



The TTG girder clamps are designed for transporting girders in the 'l' configuration / position (see photograph on the right).

These are ideal for use within steel stockholders. Once offered up to the *horizontal* flange of the girder they are locked in place by the jaw locking lever.

The design allows the clamp to be used individually, however for longer girders they should be used in pairs in conjunction with a spreader beam.



<sup>\*</sup>Per clamp.

<sup>•</sup> Please contact our sales team for full technical drawings.

Please contact our sales team for full technical drawings.

Please contact our sales team for full technical drawings.